

■ Model No. **GHP-5**

Height : 590 mm
Weight : 50.5 kgs (w/o oil)

■ Specifications:

Max. Pressure : 700 bar
Oil Required : 9.5 L
Motor Size : 6.5 HP
Valve type : 4-way, 3-position
Motor Manufacturer : Honda
Manually controlled engine

■ Oil Delivery:

13.4 L / min at low pressure
2.4 L / min at high pressure

■ Features:

- Pressure gauge can be located in upright position for better reading.
- Equipped with a 4-way, 3-position manual valve to prevent the electric control valve being locked and not able to perform retire because of high temperature.
- Supplied with a rack with rollers.
- High efficiency and fast working gasoline pump.



■ Model No. **GHP-5SD**

Height : 667 mm

Weight : 66.5 kgs (w/o oil)



■ Specifications:

Max. Pressure : 700 bar

Oil Required : 9.5 L

Motor Size : 6.5 HP

Valve type : 4-way, 3-position
Solenoid Valve

Motor Manufacturer : Honda

Manually controlled engine

**Wireless
Solenoid Valve**


■ Oil Delivery:

13.4 L / min at low pressure

2.4 L / min at high pressure

■ Features:

- Pressure gauge located in upright position for better reading.
- Supplied with inflatable tires and rotated 360° front wheels for changing direction easily.
- High efficiency and fast working gasoline pump
- Permits the user to advance, hold and retract the ram at both single and double acting presses.
- Suitable for double acting compression heads used in transmission line stringing and maintenance or single acting compression heads for overhead work fields.
- Radio Frequency remote controller is able to be used wireless at less 30 meters distance by its remote operation.



- Rotatable 360° front wheel, easy to change direction.



- Improved design of enlarged tires to eliminate bumpy road.



- Wire remote controller storage box.

**Wireless
Manual /
Solenoid Valve**



- Optional remote controller, shall order separately.

NEW



■ Model No. **GHP-5SDRM**

Height : 667 mm

Weight : 67.5 kgs (w/o oil)

■ Specifications:

Max. Pressure : 700 bar

Oil Required : 9.5 L

Motor Size : 6.5 HP

Valve type : 4-way, 3-position
Solenoid Valve

Motor Manufacturer : Honda

Manually controlled engine



• Optional remote function
(RF wireless remote / wire remote)

• Optional remote controller, shall order separately.

NEW



■ Model No. **GHP-5MR**

Height : 667 mm

Weight : 75.6 kgs (w/o oil)

■ Specifications:

Max. Pressure : 700 bar

Oil Required : 9.5 L

Motor Size : 6.5 HP


Valve type : 4-way, 3-position
Manual / Solenoid Valve

Motor Manufacturer : Honda

Manually controlled engine



• Optional remote function
(RF wireless remote / wire remote)



• Unique designed both for manual & solenoid valve switchable control.



• Unique designed both for manual & solenoid valve switchable control.

• Optional remote controller, shall order separately.

