

■ Model No. **HYCC-P85**

Length : 716 mm

Weight : 9.6 kgs

■ Specifications:

Max. Pressure : 700 bar

Oil Required : 66 cc

Max. Output : 5.47 tons / 48.7 kN

■ Cutting Capacity:

Cu strands : 28 mm

Al strands : 38 mm

CCP cable : 85 mm

Underground cable : 50 mm (Except armoured cable)

Cutting of piano wire is prohibited.

■ Features:


- Lock pin type cutting head.
- Two stage pumping action for rapid blade advance.
- 180° rotating head for convenient operation.
- Superior guillotine type cutting for less jamming than shear type cutters.
- All blades are easily replaceable.
- Spring return.
- No set-up time required.
- Light weight, self-contained tool, can be used anywhere.

■ Accessories:

Carrying Bag



HYCC-P85 #57	Moving Blade
HYCC-P85 #39	Fixed Blade



CUTTERS

■ Model No. TC-085

Length : 667 mm

Weight : 8.4 kgs

■ Specifications:

Max. Pressure : 700 bar

Oil Required : 163 cc

Max. Output : 6.23 tons / 55.4 kN

■ Cutting Capacity:

Cu strands : 85 mm

Al strands : 85 mm

CCP cable : 85 mm

Cutting of piano wire is prohibited.

■ Features:

- Two stage pumping action for rapid blade advance.
- 180° rotating head for convenient operation.
- Superior guillotine type cutting for less jamming than shear type cutters.
- All blades are easily replaceable.
- Flip-top latch for easy insertion of cutting material.
- Spring return.
- No set-up required.
- Lightweight, self-contained tool, can be used anywhere.

■ Accessories:

Carrying Bag



TC-085 #15	Moving Blade
TC-085 #1	Fixed Blade

