

CRIMPERS

■ Model No. UC-6

Length : 627 mm
Weight : 6.0 kgs

■ Specifications:

Max. Pressure : 700 bar
Oil Required : 27 cc
Max. Output : 7.03 tons / 62.5 kN
Jaw Opening : 36 mm
Max. Crimping Capacity : up to 32 mm outer diameter connector (UC-6)

■ Features:

- Light weight, compact and slim design.
- Pressure relief valve for overload protection.
- Automatic low/high-pressure conversion with rapid/slow operating motion.
- 360° rotating head for convenient operation.
- Two-stage hydraulic system reduces the number of pumps required.
- Dieless compression to crimp Anderson style connectors up to 500 MCM.

■ Accessories:

Plastic carrying case
(See page 220)



■ Model No. HU-6

Length : 475 mm
Weight : 4.1 kgs



■ Model No. UC-6FT

Length : 580 mm

Weight : 6.4 kgs

■ Specifications:

Max. Pressure : 700 bar
 Oil Required : 27 cc
 Max. Output : 7.03 tons / 62.5 kN
 Jaw Opening : 38 mm
 Max. Crimping Capacity : up to 36 mm outer diameter connector (UC-6FT)

■ Features:

- Light weight, compact and slim design.
- Pressure relief valve for overload protection.
- Automatic low/high-pressure conversion with rapid/slow operating motion.
- 360° rotating head for convenient operation.
- Two-stage hydraulic system reduces the number of pumps required.
- Dieless compression to crimp Anderson style connectors up to 750 MCM.

■ Accessories:

Plastic carrying case
 (See page 220)



■ Model No. HU-6FT

Length : 489 mm

Weight : 4.2 kgs

