



KI-PH300

■ Specifications:

Drive unit: 18V DC Motor

Charger (GS/CE):

Input voltage: 110V Single Phase AC Input voltage: 230V Single Phase AC

Input frequency: 50-60 Hz Input current: 21.75 VA Reservoir capacity: 55 cc

■ Crimping Capacity:

Max Pressure

: 6.9 tons / 61.4 kN Crimping Force

Max Compression:

300 mm² copper Aluminum lugs Accepts all dies used for Alcoa, Burndy, T&B, Klauke, Cembre and Blackburn

6 ton compressors

 Dies sold separately (T16/25/35/50/70/95/12/150/185/240/300)



Height: 450 mm Weight: 4.3 kgs (w/o battery)

■ Features:



LED Work Lights

For work area illumination to provide better vision when operating.



Operation Button

Switch for piston advance and retract



Display Panel

- 1. Pressure Indicator
- 2. Operation Counter
- 3. Auto-retract Setting
- 4. Wireless Remote Countrol Setting
- 5. Time Setting
- 6. Battery Power Indicator



USB Transmission

Transfer and review operation history.



Emergency Retract Button

Forcibly to retract during emergency situation or when the operation button loses function



Battery Seat

Operate with powerful, high-capacity Li-Ion batteries along.