

## ■ Model No. **H3**

Length : 675 mm  
Weight : 3.50 kgs  
Packaging : Box

## ■ Crimping Capacity:

- Crimping Force : 4.5 ton
- Uses D & W-style die sets.
- Storage carrying case & dies are sold separately.

## ■ Features:

- Proper crimps are assured with butting steel jaws.
- Increased strength and greater bearing area is provided with larger steel bolts.
- Fast, easy, one-hand die insertion.
- No lost W dies with spring loaded positive lock die retainer buttons.
- No lost D dies with top loaded positive locating lock.
- Full crimp force assured with over center cam action.
- Operator protection provided with butt stops and heat shrink tubing.
- Long life expectancy provided with fiberglass handles and light weight high strength aluminum alloy castings.
- Equipped with a die groove for Kearney D type die sets and includes 5/8" round die set on the top jaw.
- The "K" die groove accommodates the line of type "D" & "W" types die set inserts.



## ■ Model No. **CASE-OD3**

## ■ Connector Range :

- Copper, Aluminum, ACSR, Copperweld, Alumoweld, Steel, 6201, 5005, Compressed and Compact Conductors.
- Copper Taps : # 10 sol. -2/0 str.
- Aluminum, ACSR Taps : # 14 sol. -4/0 ACSR
- Stirrups : # 6 ACSR-4/0 ACSR
- Overhead Full Tension Deadend, Full Tension Splices, Non Tension Splices, and Terminals
- Conductor Range : # 10 str. -4/0 ACSR
- Code Conductor Connectors : # 6-4/0 str. Copper and Aluminum



KuDos KW-Dies	KW-BG	KW-O	KW-C	KW-K840	KW-161	KW-162	KW-163	KW-164
Burndy W-Dies	W-BG	W-O	W-C	W-K840	W-161	W-162	W-163	W-164
KuDos KW-Dies	KW-165	KW-166	KW-171	KW-237	KW-243	KW-247	KW-249	KW-702
Burndy W-Dies	W-165	W-166	W-171	W-237	W-243	W-247	W-249	W-702
KuDos KW-Dies	KW-241	KW-245	KW-660	KW25RT	KW26RT	KW28RT	KW2CRT	KW5CRT
Burndy W-Dies	W-241	W-245	W-660	W25RT	W26RT	W28RT	W2CRT	W5CRT