

■ Model No. PNST-10 / PNST-10M

Weight: 7.6 kgs

■ Punching Capacity:

• Max. Thickness:

Stainless Steel: 1.6 mm Steel: 3.2 mm Mild • Max. Diameter: 4 inch

· 4 inch diameter hole on 3.2 mm thickness mild steel

■ Features:

- · Suitable to punch holes in electrical panels, switchboards and others.
- · Single action cylinder with spring release.
- Fast, easy, and simple to operate.
- Compact design makes this a perfect choice for use on construction sites and maintenance jobs.
- Powerful 12.7 ton hydraulic ram.

















■ Accessories:

Model No.	Accessories	
PNST-10	 HP-180N PDV-10 Draw Stud (3/4",3/8") Spacer (S, M, L) Plastic Case 	6 Punch Die Sets: 1/2", 3/4", 1", 1-1/4", 1-1/2", 2"
PNST-10M	 HP-180N PDV-10 Draw Stud (3/4", 3/8") Spacer (S, M, L) Plastic Case 	6 Punch Die Sets: 16mm, 20mm, 25mm, 32mm, 40mm, 50mm

• Do not use HP-180N with any compression head that requires a relief valve to ensure a constant compression.

■ Punch Driver: PDV-10

Ram Stroke: 25 mm Oil Required: 47 cc

Max. Output: 14.01 tons / 124.6 kN

■ Packaging:

plastic carrying case















■ Model No. PN-052 / PN-052M

Height: 125 mm Weight: 4.5 kgs

■ Punch Driver: PDV-10

Ram Stroke: 25 mm Oil Required: 47 cc

Max. Output: 14.01 tons / 124.6 kN

■ Punching Capacity:

· Max. Thickness:

Stainless Steel: 1.6 mm Steel: 3.2 mm Mild · Max. Diameter: 4 inch

· 4 inch diameter hole on 3.2 mm thickness mild steel

· Single action cylinder with spring release

■ Features:

• Suitable to punch holes in electrical panels, switchboards and others.

- Fast, easy and simple to operate.
- · Compact design makes this a perfect choice for use on construction sites and maintenance jobs.
- Powerful 12.7 ton hydraulic ram.



■ Accessories:

Model No.	Accessories	
PN-052	 PDV-10 Draw Stud (3/4",3/8") Spacer (S, M, L) Plastic Case 	6 Punch Die Sets: 1/2", 3/4" 1", 1-1/4", 1-1/2", 2"
PN-052M	 PDV-10 Draw Stud (3/4", 3/8") Spacer (S, M, L) Plastic Case 	6 Punch Die Sets: 16mm, 20mm, 25mm, 32mm, 40mm, 50mm











■ Model No. PN-254

Weight: 11 kgs

■ PUNCH SET

• Use to punch electrical panels, switchboards and others.

Maximum panel thickness:
 3.2 mm mild steel.

• Can be operated by the Punch Driver PDV-10.

• Complete with a plastic carry case.

Include:

Punch die: 2¹/₂", 3", 3¹/₂", 4"

total 4 sets.

1 set of draw stud 3/4" / 1/2" and 1/2" NUT each.





■ Model No. **DRCP-559140**

Length: 111 cm Weight: 9.2 kgs

■ Cutting Capacity:

- · Suitable for cutting 5 different shapes of DINrail sections without burrs or deformation.
- Ruler and Stopper are supplied with this tool.
- This tool can punch 8.8 mm x 5 mm holes along or perpendicular to the axis of the rail.

■ Features:

- Fast and easy cutting of DIN-rails for mounting electric components free of burrs.
- · Delivered complete with a length stop gauge and punch set for mounting-holes.















